

CONTINUOUS POLY BAG MACHINE

## servo X/servo 800 THE FLEXIBLE HIGH-END ALL-ROUNDER











## servo X servo 800

These machines cover the broadest possible range of horizontal film packaging applications with side sealing - from business card through to windscreen - and they still have maximum flexibility.

The servo 800 is the most flexible and powerful of machines in the large-format segment. Both machine types feature infeed belts processing a wide range of products.

The machines win over with their continuous packaging process and no stop-and-go, meaning dead time is not an issue when sealing. This ensures that the film packaging's excellent appearance is outstanding. Besides high performance, the availability is extremely high.

## **HIGHLIGHTS**

- Minimum product spacing for maximum film saving thanks to precision synchronisation of the transverse sealing unit and product
- Easy line integration and connectivity with higher-level systems, Industry 4.0 Ready
- Siemens TIA Portal
- Smart user guidance via CoPilot and touch screen
- Optimum film feed for processing the most diverse of film types and grades
- Maximum serviceability and maintainability thanks to perfect access and numerous maintenance-free components



TECHNICAL DATA	
Product infeed	manual as standalone/automatic in line
Film	PE, PO, PP, biofilms, centre-folded film and flat film
Product size	<b>servo X:</b> L: from 45 mm, W: 10 – 450 mm, H: max. 250 mm <b>servo 800:</b> L: from 150 mm, W: 150 – 800 mm, H: max. 450 mm
Operation	continuous
Capacity	servo X: up to 8.000 cycles/h servo 800: up to 5.000 cycles/h

